

Reviewed on 11/24/2010

1 Identification

· Product identifier

· Trade name: xylene

· Article number: 2425

· CAS Number: 1330-20-7

· EC number: 215-535-7

Index number: 601-022-00-9

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the preparation

Chemical for research, development, manufacturing and analysis

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Biosolve B.V.

Leenderweg 78, 5555 CE Valkenswaard, the Netherlands.

Tel: +31-(0)40-2071300 Fax:+31-(0)40-2048537

Email: info@biosolve-chemicals.com

Biosolve Chimie

20 Rue Roger Husson, 57260 Dieuze, France Tel: +33 3 878 675 80/81/82/83/84/85 Email: info@biosolvechimie.com

Bio-Lab Ltd.

POB 34038, Jerusalem 91340, Israel

Tel: + 972 -2- 584 1111 Fax: + 972 -2- 584 1110

Email: info@biolab-chemicals.com

- · Information department: Product safety department
- · Emergency telephone number: During normal opening times: +972 2 584 1111

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

H226 Flammable liquid and vapour.



GHS07

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Harmful

Harmful by inhalation and in contact with skin.



Irritating to skin.

(Contd. on page 2)

(Contd. of page 1)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/15/2013 Reviewed on 11/24/2010

Trade name: xylene

Highly flammable

Flammable.

- · Information concerning particular hazards for human and environment: Not applicable.
- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:





Harmful Highly flammable

· Risk phrases:

Flammable.

Harmful by inhalation and in contact with skin. Irritating to skin.

· Safety phrases:

Keep away from sources of ignition - No smoking. Avoid contact with eyes. Do not empty into drains.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2Fire = 3

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

1330-20-7 xylene

- Identification number(s)
- · EC number: 215-535-7
- · Index number: 601-022-00-9

4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)



Printing date 08/15/2013 Reviewed on 11/24/2010

Trade name: xylene

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)



Reviewed on 11/24/2010

Trade name: xylene

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm

BEI

Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine Medium: urine Time: end of shift

Parameter: Methylhippuric acids

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles



Reviewed on 11/24/2010

Trade name: xylene

(Contd. of page 4)

Information on basic physical and c	chemical properties		
General Information			
Appearance:			
Form:	Liquid		
Color:	Colorless		
Odor:	Aromatic Not determined.		
Odour threshold:			
pH-value:	Not determined.		
Change in condition			
Melting point/Melting range:	>-34 °C (>-29 °F)		
Boiling point/Boiling range:	140 °C (284 °F)		
Flash point:	25 °C (77 °F)		
Flammability (solid, gaseous):	Not applicable.		
Ignition temperature:			
Decomposition temperature:	Not determined.		
Auto igniting:	Not determined.		
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.		
Explosion limits:			
Lower:	1 Vol %		
Upper:	7 Vol %		
Vapor pressure at 20 °C (68 °F):	10 hPa (8 mm Hg)		
Density:	Not determined.		
Relative density	Not determined.		
Vapour density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with			
Water at 20 °C (68 °F):	0.2~g/l		
Partition coefficient (n-octanol/wate	er): Not determined.		
Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
Other information	No further relevant information available.		

10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

- USA



Reviewed on 11/24/2010

Trade name: xylene

(Contd. of page 5)

3

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values	that	are	relevant	for	classi	fication:
-----------	--------	------	-----	----------	-----	--------	-----------

 Oral
 LD50
 2840 mg/kg (rat)

 Dermal
 LD50
 > 4350 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

1330-20-7 xylene

· NTP (National Toxicology Program) Substance is not listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- **ADR** UN1307
- · UN proper shipping name
- · **ADR** 1307 Xylenes
- · Transport hazard class(es)
- · DOT



Class 3 Flammable liquids.

(Contd. on page 7)



rte 08/15/2013 Reviewed on 11/24/2010

Trade name: xylene

(Contd. of page 6) · Label 3 \cdot ADR · Class 3 (F1) Flammable liquids · Label · IMDG, IATA 3 Flammable liquids. · Class · Label 3 · Packing group II \cdot **DOT** Ш · ADR, IMDG, IATA · Environmental hazards: · Marine pollutant: No Warning: Flammable liquids Special precautions for user Danger code (Kemler): F-ES-D · EMS Number: · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. UN1307, Xylenes, 3, III UN "Model Regulation":

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- ·Sara
- · Section 355 (extremely hazardous substances): Substance is not listed.
- · Section 313 (Specific toxic chemical listings): Substance is not listed.
- · TSCA (Toxic Substances Control Act): Substance is not listed.
- Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.
- · Carcinogenic categories

EPA (Environmental Protection Agency)	
1330-20-7 xylene	I
TIV (Throshold I imit Value established by ACCIH)	

- TLV (Threshold Limit Value established by ACGIH)

 1330-20-7 | xylene
- NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed. OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.
- Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 8)



ng date 08/15/2013 Reviewed on 11/24/2010

Trade name: xylene

(Contd. of page 7)

· Hazard symbols:





Harmful Highly flammable

· Risk phrases:

Flammable.

Harmful by inhalation and in contact with skin.

Irritating to skin.

· **Safety phrases:**Keep away from sources of ignition - No smoking.

Avoid contact with eyes.

Do not empty into drains.

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department
- · Contact: Product safety department
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

USA