

Reviewed on 05/09/2010

1 Identification

· Product identifier

· Trade name: Deblock DCA in Toluene

· Article number: 0435, 2732

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the preparation

Chemical for research, development, manufacturing and analysis

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Biosolve B.V.

Leenderweg 78, 5555 CE Valkenswaard, the Netherlands.

Tel: +31-(0)40-2071300 *Fax:*+31-(0)40-2048537

Email: info@biosolve-chemicals.com

Biosolve Chimie

20 Rue Roger Husson, 57260 Dieuze, France Tel: +33 3 878 675 80/81/82/83/84/85 Email: info@biosolvechimie.com

Bio-Lab Ltd.

POB 34038, Jerusalem 91340, Israel

Tel: + 972 -2- 584 1111 Fax: + 972 -2- 584 1110

Email: info@biolab-chemicals.com

- · Information department: Product safety department
- · Emergency telephone number: During normal opening times: +972 2 584 1111

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

H225 Highly flammable liquid and vapour.



GHS08 Health hazard

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.



GHS05 Corrosion

H318 Causes serious eye damage.



GHS07

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



(Contd. on page 2)



Printing date 08/15/2013 Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

(Contd. of page 1)

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.



Irritant

Irritating to eyes and skin.



Highly flammable

Highly flammable.

Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:





Harmful Highly flammable

· Hazard-determining components of labeling:

toluene

· Risk phrases:

Highly flammable.

Irritating to eyes and skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)



Printing date 08/15/2013 Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
108-88-	3 toluene	75-100%
	♠ H225; ♦ H361; H373; H304; ♦ H315; H336	
79-43-	dichloroacetic acid	2.5-10%
	♦ H314	

4 First-aid measures

- Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · **Protective equipment:** No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 08/15/2013 Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

108-88-3 toluene

PEL Short-term value: C 300; 500* ppm

Long-term value: 200 ppm *10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm TLV Long-term value: 75 mg/m³, 20 ppm

BEI

79-43-6 dichloroacetic acid

TLV Long-term value: 2.64 mg/m³, 0.5 ppm

Skin

Ingredients with biological limit values:

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)



Printing date 08/15/2013 Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

(Contd. of page 4)

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and · General Information	chemical properties	
· Appearance:		
Form:	Fluid	
Color:	According to product specification	
· Odor:	Characteristic	
Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	-95 °C (-139 °F)	
Boiling point/Boiling range:	110 °C (230 °F)	
· Flash point:	4 °C (39 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	535 °C (995 °F)	
Decomposition temperature:	Not determined.	

(Contd. on page 6)



Printing date 08/15/2013 Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

	(Contd. of page
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapon mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
Vapor pressure at 20 °C (68 °F):	29 hPa (22 mm Hg)
Density at 20 °C (68 °F):	0.8907 g/cm³ (7.433 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 15 °C (59 °F):	0.5~g/l
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	97.0 %
VOC content:	97.0 %
	864.0 g/l / 7.21 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

LD/LC30 values that are relevant for classification:		
108-88-3 toluene		
)ral	LD50	5000 mg/kg (rat)
)ermal	LD50	12124 mg/kg (rabbit)
nhalative	LC50/4 h	5320 mg/l (mouse)
9–43–6 di	chloroacet	ic acid
)ral	LD50	2820 mg/kg (rat)
Permal	LD50	510 mg/kg (rabbit)
	98-88-3 t oral ermal chalative 9-43-6 di ral	08-88-3 toluene ral LD50 ermal LD50 thalative LC50/4 h 0-43-6 dichloroacet ral LD50

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 7)



Printing date 08/15/2013 Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

· Additional toxicological information:

(Contd. of page 6)

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
108-88-3	toluene	3
79-43-6	dichloroacetic acid	2B
· NTP (Nat	tional Toxicology Program)	
None of the ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1993	
UN proper shipping name		
DOT	Flammable liquids, n.o.s. (Toluene)	
ADR	1993 Flammable liquids, n.o.s. (Toluene)	
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (TOLUENE)	

- HSA



Printing date 08/15/2013 Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

(Contd. of page 7)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids.

· Label

· ADR



· Class 3 (F1) Flammable liquids

· Label

· IMDG, IATA



· Label

· Class 3 Flammable liquids.

3

· Packing group

· **DOT, ADR, IMDG, IATA**

Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 33 · EMS Number: F-E,S-E

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

• UN "Model Regulation": UN1993, Flammable liquids, n.o.s. (Toluene), 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

108-88-3 toluene

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

79-43-6 dichloroacetic acid

(Contd. on page 9)



Printing date 08/15/2013 Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

Chemicals known to cause reproductive toxicity for females:

108-88-3 | toluene

• Chemicals known to cause reproductive toxicity for males:

79-43-6 | dichloroacetic acid

• Chemicals known to cause developmental toxicity:

108-88-3 | toluene

Carcinogo	enic categories	
EPA (Env	vironmental Protection Agency)	
108-88-3	toluene	I
79-43-6	dichloroacetic acid	I
TLV (Thr	reshold Limit Value established by ACGIH)	·
108-88-3	toluene	A
79-43-6	dichloroacetic acid	<i>A</i> .
NIOSH-C	Ca (National Institute for Occupational Safety and Health)	
None of th	he ingredients is listed.	
OSHA-Ca	a (Occupational Safety & Health Administration)	
None of th	he ingredients is listed.	

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:





Harmful Highly flammable

· Hazard-determining components of labeling:

toluene

· Risk phrases:

Highly flammable.

Irritating to eyes and skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department
- · Contact: Product safety department
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)



Reviewed on 05/09/2010

Trade name: Deblock DCA in Toluene

(Contd. of page 9)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

USA