

Printing date 08/14/2013

Reviewed on 08/14/2013

1 Identification

· Product identifier

• Trade name: Deblock DCA 2.5-10% in Toluene

· Article number: 2307, 2733

Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

Application of the substance / the preparation Chemical for research, development, manufacturing and analysis

• Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Biosolve B.V. Leenderweg 78, 5555 CE Valkenswaard, the Netherlands. *Tel:* +31-(0)40-2071300 Fax:+31-(0)40-2048537 Email: info@biosolve-chemicals.com

Biosolve Chimie 20 Rue Roger Husson, 57260 Dieuze, France *Tel:* +33 3 878 675 80/81/82/83/84/85 Email: info@biosolvechimie.com

Bio-Lab Ltd. POB 34038, Jerusalem 91340, Israel *Tel:* + 972 - 2- 584 1111 Fax: + 972 - 2- 584 1110 Email: info@biolab-chemicals.com

· Information department: Product safety department • Emergency telephone number: During normal opening times: +972 2 584 1111

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame H225 Highly flammable liquid and vapour. GHS08 Health hazard H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. GHS05 Corrosion H314 Causes severe skin burns and eye damage. GHS07 H336 May cause drowsiness or dizziness. · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Corrosive Causes burns. (Contd. on page 2) USA

(Contd. of page 1)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/14/2013

Trade name: Deblock DCA 2.5-10% in Toluene

Harmful

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.



Highly flammable

Highly flammable.

Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

- The product has to be labeled due to the calculation procedure of international guidelines.
- Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· Label elements

· Labelling according to EU guidelines: The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:



Corrosive Highly flammable

· Hazard-determining components of labeling:

toluene dichloroacetic acid

· Risk phrases:

Highly flammable. Causes burns. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

· Safety phrases:


Keep locked up and out of the reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing, gloves and eye/face protection.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· Classification system:





Health = 3Fire = 3*Reactivity* = 0

HMIS-ratings (scale 0 - 4)



- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)

USA



Reviewed on 08/14/2013

Trade name: Deblock DCA 2.5-10% in Toluene

• **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
108-88-3	toluene	75-100%
	🚸 H225; 🚸 H361; H373; H304; 🚸 H315; H336	
79-43-6	dichloroacetic acid	2.5-10%
	H314	

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- *After inhalation:* In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- *After swallowing:* Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to item 13

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4)

(Contd. of page 2)

USA -

(Contd. of page 3)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/14/2013

Trade name: Deblock DCA 2.5-10% in Toluene

See Section 13 for disposal information.

7 Handling and storage

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- *Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace: 108-88-3 toluene PEL Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift REL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm TLV Long-term value: 75 mg/m³, 20 ppm BEI 79-43-6 dichloroacetic acid TLV Long-term value: 2.64 mg/m³, 0.5 ppm Skin · Ingredients with biological limit values: 108-88-3 toluene BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/LMedium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) • Additional information: The lists that were valid during the creation were used as basis. (Contd. on page 5)

- USA



Reviewed on 08/14/2013

Trade name: Deblock DCA 2.5-10% in Toluene

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:

General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Information on basic physical and	chemical properties	
General Information		
Appearance:		
Form:	Solution	
Color:	Colorless to slightly yellow	
Odor:	Aromatic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	-95 °C (-139 °F)	
Boiling point/Boiling range:	110 °C (230 °F)	
Flash point:	4 °C (39 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	535 °C (995 °F)	
Decomposition temperature:	Not determined.	

Reviewed on 08/14/2013

Page 6/10

Trade name: Deblock DCA 2.5-10% in Toluene

A	(Contd. of page
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
Vapor pressure at 20 °C (68 °F):	29 hPa (22 mm Hg)
Density at 20 °C (68 °F):	0.9045 g/cm ³ (7.548 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 15 °C (59 °F):	0.5 g/l
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	95.0 %
VOC content:	95.0 %
	859.3 g/l / 7.17 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

108-88-3 t Oral	LD50	5000 ma/kg (ngt)	
		5000 mg/kg (rat)	
Dermal	LD50	12124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5320 mg/l (mouse)	
79 - 43-6 di	chloroace	ic acid	
Oral	LD50	2820 mg/kg (rat)	
Dermal	LD50	510 mg/kg (rabbit)	
on the eye	1: Caustic Strong ca	c t: effect on skin and mucous membranes. ustic effect. sitizing effects known.	
••••		0.00	(Contd. on page

(Contd. on page 7)

USA

(Contd. of page 6)

3

2B



Safety Data Sheet acc. to OSHA HCS

Printing date 08/14/2013

Reviewed on 08/14/2013

Trade name: Deblock DCA 2.5-10% in Toluene

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

108-88-3 toluene

79-43-6 dichloroacetic acid

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

• Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

• **Recommendation:** Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN2924
· UN proper shipping name	
DOT	Flammable liquids, corrosive, n.o.s. (Toluene, Dichloroaceti acid)
· ADR	2924 Flammable liquids, corrosive, n.o.s. (Toluene Dichloroacetic acid)
· IMDG, IATA	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (TOLUENE DICHLOROACETIC ACID)

[·] Uncleaned packagings:



Reviewed on 08/14/2013

Trade name: Deblock DCA 2.5-10% in Toluene

	(Contd. of page
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids.
Label	3+8
ADR	
Class	3 (FC) Flammable liquids
Label	3+8
Class	3 Flammable liquids.
Label	3+8
Packing group	
DOT, ĂĎR, ÎMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler): EMS Number:	338 F-E,S-C
EMS Number: Segregation groups	F-E,S-C Acids
Transport in bulk according to Ann MARPOL73/78 and the IBC Code	<i>ex II of</i> Not applicable.
UN "Model Regulation":	UN2924, Flammable liquids, corrosive, n.o.s. (Toluen Dichloroacetic acid), 3 (8), II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

108-88-3 toluene

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

79-43-6 dichloroacetic acid

(Contd. on page 9)

- USA



Reviewed on 08/14/2013

Trade name: Deblock DCA 2.5-10% in Toluene

	(Contd. of page
Chemicals known to cause reproductive toxicity for females:	
108-88-3 toluene	
Chemicals known to cause reproductive toxicity for males:	
79-43-6 dichloroacetic acid	
Chemicals known to cause developmental toxicity:	
108-88-3 toluene	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
108-88-3 toluene	
79-43-6 dichloroacetic acid	
TLV (Threshold Limit Value established by ACGIH)	
108-88-3 toluene	A
79-43-6 dichloroacetic acid	A
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:



· Hazard-determining components of labeling: toluene dichloroacetic acid

Corrosive

· Risk phrases:

Highly flammable. Causes burns. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep locked up and out of the reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing, gloves and eye/face protection.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Product safety department

· Contact: Product safety department

(Contd. on page 10)

USA

(Contd. of page 9)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/14/2013

Trade name: Deblock DCA 2.5-10% in Toluene

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organization
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
USA